


# York Kitchen Mixer Hook Spout

Nero




Lead Free



Versions:202506



## Drawing



## Specifications

### Watermark License

WM-060073

### Temperature Rating

Min 1°C-Max 75°C

### Pressure Rating

Min 150kpa - Max 500kpa

## Finish & SKU



CHROME WITH WHITE PORCELAIN LEVER  
NR69210701CH



MATTE BLACK WITH WHITE PORCELAIN LEVER  
NR69210701MB



AGED BRASS WITH WHITE PORCELAIN LEVER  
NR69210701AB



BRUSHED NICKEL WITH WHITE PORCELAIN LEVER  
NR69210701BN



CHROME WITH BLACK PORCELAIN LEVER  
NR69210703CH



CHROME WITH METAL LEVER  
NR69210702CH



MATTE BLACK WITH METAL LEVER  
NR69210702MB



AGED BRASS WITH METAL LEVER  
NR69210702AB



BRUSHED NICKEL WITH METAL LEVER  
NR69210702BN

\*Dimensions are nominal measurements only.

## Packaging Includes


1x Kitchen Mixer  
2x Flexible Hoses  
1x Installation Kit

# Installation Instruction

IMPORTANT: Read all instructions before installing.

## GENERAL INSTRUCTIONS:

- This product must be installed by a licensed plumber. Ensure that your plumbing installation conforms to the Australian/New Zealand Standard AS/NZS 3500.
- All pipework must be thoroughly flushed prior to the installation of the mixer. In-line filters must be fitted on both hot and cold supplies to prevent foreign particles from damaging the ceramic cartridge.
- All outlets used primarily for personal hygiene must deliver water at a safe temperature in accordance with regional regulations.



## NOTE:

- Do not hydrostatic test the installation with this mixer installed. Damage to the ceramic cartridge may occur.
- Do not remove the ceramic cartridge from the mixer when installing.
- After installation, all connections must be checked for leaks.
- This mixer is not recommended for use in uncontrolled heating systems such as wet-backs or solar heating units unless a suitable tempering valve is fitted.
- If limited water flow is experienced, locate aerator and filter washers and clean away foreign material as required.
- It is the responsibility of the plumber to ensure a waterproof seal is achieved between the product and mounting surface. If in doubt about the quality of the seal, remove the product and reinstall.

## Installation Instruction:

- 1.Screw the flexible hoses into the mixer body, and fully hand tighten.
- 2.Pass the tail of flexible pipes through the hole on the bench top from above, and place the mixer in position on the bench top. Inspect to see if any alteration to the existing supply pipe work is required. Make any necessary alterations.
- 3.Tighten the fixing nut to treaded pipes compressing the galvanized washer and rubber washer from the under-side of the counter. Then tighten the 2 screws on the fixing nut.
- 4.Check that the mixer body is positioned correctly, fully tighten the fixing nut screw and fixing bolts firmly.
- 5.Connect the water supply pipes to the tail of flexible hoses with the hot water and cold water. Make sure the o-ring in the base ring seals completely around the hole in the mounting surface
- 6.Test for any leaks.

## MAINTENANCE AND CARE:

- Regularly check the mixer and connections for signs of wear or leaks.
- Clean the tap with mild soapy water to maintain its appearance, avoiding harsh chemicals and abrasive materials that may damage the finish.

## FINAL INSPECTION:

- Ensure the tap operates smoothly and that there are no leaks at the connections.
- Clean the area and the newly installed tap with a soft cloth to remove any installation residues.

# Nero

